

# CONCEPTS'24



## BOOK OF ABSTRACTS

**1<sup>st</sup>** International Joint Conference  
on Conceptual Knowledge Structures  
September 10th - 13th, 2024. Cádiz, Spain

Editors:

Inma P. Cabrera, Sébastien Ferré, Jesús Medina, Sergei Obiedkov





# Book of abstracts of CONCEPTS 2024

© Inma P. Cabrera, Sébastien Ferré, Jesús Medina, Sergei Obiedkov, Editors

Edition 1<sup>st</sup>  
First published: 2024

ISBN: 978-84-09-63916-8  
Published and printed by:  
Universidad de Cádiz (Dept. Matemáticas), Spain.



# Table of Contents

<b>Keynote:</b> Multi-adjoint Formal Concept Analysis. Theory and Applications . . . . .	1
<i>Mar a Eugenia Cornejo Pinero</i>	
Subdirectly irreducible and semisimple double Boolean algebras . . . . .	2
<i>Leonard Kwuida, Etienne Romuald Temgoua Alomo</i>	
The Birkhoff completion of finite lattices . . . . .	3
<i>Mohammad Abdulla, Johannes Hirth and Gerd Stumme</i>	
Arrow relations in lattices of integer partitions . . . . .	4
<i>Asma'a Almazaydeh, Mike Behrisch, Edith Vargas-Garc a, Andreas Wachtel</i>	
Conceptual knowledge modelling for human–AI teaming in data–frugal industrial environments . . . . .	5
<i>Vedran Galetic, Dylan Sheldon, Alistair Nottle</i>	
Handling knowledge over moving object trajectories using Formal Concept Analysis . . . . .	6
<i>Rouaa Wannous, Salah Eddine Boukhetta, Cecile Vincent</i>	
FCAvizIR: Exploring relational data set’s implications using metrics and topics . . . . .	7
<i>Lola Musslin, Alexandre Bazin, Marianne Huchard, Pierre Martin, Pascal Poncelet, Vincent Raveneau, Arnaud Sallaberry</i>	
Realizability of rectangular Euler diagrams . . . . .	8
<i>Dominik Dürschnabel, Uta Priss</i>	
Spanning concept trees: algorithms and interaction . . . . .	9
<i>Tim Pattison</i>	
A repository for formal contexts . . . . .	10
<i>Tom Hanika, Robert Jäschke</i>	
<b>Keynote:</b> Contextual Attribute Logics . . . . .	11
<i>Bernhard Ganter</i>	
Exploring the 3-dimensional variability of websites’ user-stories using Triadic Concept Analysis . . . . .	12
<i>Alexandre Bazin, Thomas Georges, Marianne Huchard, Pierre Martin and Chouki Tibermacine</i>	

Exploring old arabic remedies with Formal and Relational Concept Analysis .....	13
<i>Vanessa Fokou, Karim El Ha , Agnes Braud, Xavier Dolques, Florence Le Ber, Veronique Pitchon</i>	
Conceptual mapping of controversies .....	14
<i>Claude Draude, Dominik Darrschnabel, Johannes Hirth, Viktoria Horn, Jonathan Kropf, Jörn Lamla, Gerd Stumme and Markus Uhlmann</i>	
Towards a generalized modus ponens based on the $\varphi$ -index of inclusion ..	15
<i>Carolina Diaz-Montarroso, Nicolas Madrid, Elo sa Ram rez-Poussa</i>	
Efficiency of fuzzy decision algorithms based on the strength of decision rules .....	16
<i>Fernando Chacon-Gomez, Maria Eugenia Cornejo Piñero, Jesus Medina</i>	
Comparing Relational Concept Analysis and Graph-FCA on their common ground .....	17
<i>Vanessa Fokou, Peggy Cellier, Xavier Dolques, Sebastien Ferre, Florence Le Ber</i>	
What can FCA-based Boolean matrix factorization do for object-attribute biclustering? .....	18
<i>Martin Trnecka, Roman Vyjidacek</i>	
Analyzing the relationship between the factorization of formal contexts and independent subcontexts .....	19
<i>Roberto G. Aragon, Jesus Medina and Elo sa Ram rez-Poussa</i>	
<b>Keynote:</b> Interactions between the psychology of concepts and conceptual exploration of data .....	20
<i>Radim Belohlavek</i>	
Rearrangement of fuzzy formal contexts for reducing cost of algorithms ..	21
<i>Lopez-Rodríguez, Manuel Ojeda-Hernandez</i>	
Enhancing JAAD with knowledge graphs for improved pedestrian crossing predictions .....	22
<i>Sandra Victor, Gowrishankar Ganesh, Madalina Croitoru</i>	
Symbolic artificial intelligence for schema therapy using knowledge graphs	23
<i>Madalina Croitoru, Nathalie Blanc, Royce Anders</i>	
Semantic explorations in factorizing Boolean data via formal concepts ..	24
<i>Radim Belohlavek, Martin Trnecka</i>	

Description lattices of generalised convex hulls . . . . .	25
<i>Christophe Demko, Karell Bertet, Jean-Francois Viaud, Cyril Faucher, Damien Mondou</i>	
Shapley value in classification problems with Triadic Formal Concept Analysis . . . . .	26
<i>Martin Walo Kemgne, Blaise Bleriot Koguep Njionou, Leonard Kwuida, Dmitry I. Ignatov</i>	
What is the <i>intrinsic</i> dimension of your binary data? – and how to compute it quickly . . . . .	27
<i>Tom Hanika, Tobias Hille</i>	
Aggregation of fuzzy graphs . . . . .	28
<i>Francisco Javier Talavera, Carlos Bejines, Sergio Ardanza-Trevijano and Jorge Elorza</i>	
Bimorphisms and attribute implications in heterogeneous formal contexts . . . . .	29
<i>L'ubomir Antoni, Peter Elias, Jan Gunis, Dominika Kotlarova, Stanislav Krajci, Ondrej Kr dlo, Pavol Sokol and L'ubomir Snajder</i>	
Discovering the structure of odorants in <i>caenorhabditis elegans</i> using Formal Concept Analysis . . . . .	30
<i>Emma Reyner-Fuentes, Carmen Pelaez-Moreno, Francisco Jose Valverde-Albacete</i>	
Exploiting Formal Concept Analysis for data modeling in data lakes . . . . .	31
<i>Anes Bendimerad, Romain Mathonat, Youcef Remil, Mehdi Kaytoue</i>	
Document classification via stable graph patterns and conceptual AMR graphs . . . . .	32
<i>Eric George Parakal, Egor Dudyrev, Sergei O. Kuznetsov, Amedeo Napoli</i>	
Interpretability of formal concepts in word co-occurrence matrices . . . . .	33
<i>Akihiro Maeda, Takuma Torii and Shohei Hidaka</i>	
Computing stable extensions of argumentation frameworks using Formal Concept Analysis . . . . .	34
<i>Sergei Obiedkov and Baris Sertkaya</i>	
On the impact of sup-compositions in the resolution of multi-adjoint relation equations . . . . .	35
<i>David Lobo, Victor Lopez-Marchante, Jesus Medina</i>	
<b>Keynote:</b> How to agree to disagree: managing conceptual diversity using standpoint logic . . . . .	36
<i>Sebastian Rudolph</i>	

Connecting concept lattices with bonds between $L$ -fuzzy formal contexts by external information . . . . .	37
<i>Ondrej Kráľo, Domingo López-Rodríguez, Lubomír Antoni, Peter Elias, Stanislav Krajčí, Manuel Ojeda-Aciego</i>	
Fuzzy relational Galois connections between fuzzy transitive digraphs . . . .	38
<i>Inma P. Cabrera, Pablo Cordero, Emilio Muñoz-Velasco, Manuel Ojeda-Aciego, Bernard de Baets</i>	
Representation of double Boolean algebra: a summarization and ongoing work . . . . .	39
<i>Prosenjit Howlader, Churn Jung Liau, and Mohua Banerjee</i>	
Concept-forming operators of multi-adjoint concept lattices with hedges .	40
<i>M. Eugenia Cornejo, Jesus Medina and Francisco Jose Ocaña</i>	
Polyadic Relational Concept Analysis . . . . .	41
<i>Alexandre Bazin, Jessie Galasso and Giacomo Kahn</i>	
A formalization of multi-label classification in terms of Lattice Theory and Information Theory: concerning datasets . . . . .	42
<i>Francisco Jose Valverde-Albacete, Carmen Pelaez-Moreno</i>	



## Program Committee

Cristina Alcalde	University of Basque Country, Spain
Alexandre Bazin	University of Montpellier, France
Sadok Ben Yahia	Tallinn University of Technology, Estonia
Karell Bertet	La Rochelle University, France
Peggy Cellier	INSA Rennes, France
Pablo Cordero	University of Málaga, Spain
María Eugenia Cornejo Piñero	University of Cádiz, Spain
Miguel Couceiro	University of Lorraine, France
Christophe Demko	La Rochelle University, France
Xavier Dolques	University of Strasbourg, France
Bernhard Ganter	Ernst-Schröder-Zentrum für Begriffliche Wissensverarbeitung e.V., Darmstadt, Germany
Mohamed Hamza Ibrahim	University of Quebec in Outaouais, Canada
Tom Hanika	University of Kassel, Germany
Dmitry Ignatov	HSE University, Moscow, Russia
Jan Konecny	Palacký University Olomouc, Czech Republic
Francesco Kriegel	TU Dresden, Germany
Markus Krötzsch	TU Dresden, Germany
Leonard Kwuida	Bern University of Applied Sciences, Switzerland
Florence Le Ber	University of Strasbourg, France
Domingo López-Rodríguez	University of Málaga, Spain
Pierre Martin	University of Montpellier, France
Jesús Medina	University of Cádiz, Spain
Engelbert Mephu Nguifo	University Clermont Auvergne, France
Jan Outrata	Palacký University Olomouc, Czech Republic
Eloisa Ramírez-Poussa	University of Cádiz, Spain
Sebastian Rudolph	TU Dresden, Germany
Christian Sacarea	Babes-Bolyai University, Romania
Baris Sertkaya	Frankfurt University of Applied Sciences, Germany
Henry Soldano	Université Sorbonne Paris Nord, France
Martín Trnecka	Palacký University Olomouc, Czech Republic
Petko Valtchev	Université du Québec à Montréal, Canada
Francisco J. Valverde-Albacete	Rey Juan Carlos University, Spain



**Program of the**  
**1<sup>st</sup> International Joint Conference**  
**on Conceptual Knowledge Structures**

September 10<sup>th</sup> - 13<sup>th</sup>, 2024. Cádiz, Spain

<b>TUESDAY 10<sup>th</sup></b>	
<b>Location: Aulario "La Bomba" (Building 1812)</b>	
9:00–9:50	<b>Keynote Speaker - M. Eugenia Cornejo</b> Title: Multi-adjoint Formal Concept Analysis. Theory and Applications Chairperson: Manuel Ojeda-Aciego
9:50–10:50	<b>Session 1.</b> Chairperson: Inma P. Cabrera
	<i>Sub-directly irreducible and semi-simple double Boolean algebras</i> Leonard Kwuida, Etienne Romuald Temgoua Alomo
	<i>The Birkhoff completion of finite lattices</i> Mohammad Abdulla, Johannes Hirth, Gerd Stumme
	<i>Arrow Relations in Lattices of Integer Partitions</i> Asma'a Almazaydeh, Mike Behrisch, Edith Vargas-García, Andreas Wachtel
10:50–11:10	<b>Coffee break</b>
11:10–13:10	<b>Session 2</b> Chairperson: Gerd Stumme
	<i>Conceptual Knowledge Modelling for Human-AI Teaming in Data-Frugal Industrial Environments</i> Vedran Galetic, Dylan Sheldon, Alistair Nottle
	<i>Handling Knowledge over Moving Object Trajectories using Formal Concept Analysis</i> Rouaa Wannous, Salah Eddine Boukhetta, Cécile Vincent
	<i>FCAvizIR: Exploring Relational Data Set's Implications using Metrics and Topics</i> Lola Musslin, Alexandre Bazin, Marianne Huchard, Pierre Martin, Pascal Poncelet, Vincent Raveneau, Arnaud Sallaberry
	<i>Realizability of Rectangular Euler Diagrams</i> Dominik Dürschnabel, Uta Priss
	<i>Spanning Concept Trees: Algorithms and Interaction</i> Tim Pattison
	<i>A Repository for Formal Contexts</i> Tom Hanika, Robert Jäschke
13:10–15:15	<b>Lunch</b>
15:15–16:00	<b>Workshop LBCS</b> <b>Keynote Speaker { Peter Eklund</b> Title: Conceptual Knowledge and large language models Chairperson: L'ubomir Antoni
16:00–17:45	Workshop LBCS
18:00–20:30	<b>Cadiz Tour</b>

<b>WEDNESDAY 11<sup>th</sup></b>	
<b>Location: Aulario "La Bomba" (Building 1812)</b>	
9:00–10:00	<b>Keynote Speaker - Bernhard Ganter</b> Title: Contextual Attribute Logics Chairperson: Jesús Medina
10:00–11:00	<b>Session 3</b> Chairperson: Dominik Dürschnabel
	<i>Exploring the 3-Dimensional Variability of Websites' User-Stories using Triadic Concept Analysis</i> Alexandre Bazin, Thomas Georges, Marianne Huchard, Pierre Martin and Chouki Tibermacine
	<i>Exploring Old Arabic Remedies with Formal and Relational Concept Analysis</i> Vanessa Fokou, Karim El Haff, Agnès Braud, Xavier Dolques, Florence Le Ber, Véronique Pitchon
	<i>Conceptual Mapping of Controversies</i> Claude Draude, Dominik Dürschnabel, Johannes Hirth, Viktoria Horn, Jonathan Kropf, Jörn Lamla, Gerd Stumme, Markus Uhlmann
11:00–11:20	<b>Coffee break</b>
11:20–12:55	<b>Session 4</b> Chairperson: Sébastien Ferré
	<i>Towards a generalized modus ponens based on the <math>\varphi</math>-index of inclusion</i> Carolina Díaz-Montarroso, Nicolás Madrid, Eloísa Ramírez-Poussa
	<i>Efficiency of fuzzy decision algorithms based on the strength of decision rules</i> Fernando Chacón-Gómez, María Eugenia Cornejo Piñero, Jesús Medina
	<i>Comparing Relational Concept Analysis and Graph-FCA on their common ground</i> Vanessa Fokou, Peggy Cellier, Xavier Dolques, Sébastien Ferré, Florence Le Ber
	<i>What can FCA-based Boolean matrix factorization do for object-attribute biclustering?</i> Martin Trnecka, Roman Vyjidacek
	<i>(Kw) Analyzing the relationship between the factorization of formal contexts and independent subcontexts</i> Roberto G. Aragón, Jesús Medina and Eloísa Ramírez-Poussa
13:00–20:00	<b>Excursion including the lunch</b>

<b>THURSDAY 12<sup>th</sup></b>	
<b>Location: Aulario "La Bomba (Building 1812)</b>	
9:00–10:00	<b>Keynote Speaker - Radim Belohlavek</b> Title: Interactions between the psychology of concepts and conceptual exploration of data Chairperson: Pablo Cordero
10:00–11:00	<b>Session 5</b> Chairperson: Karel Bertet
	<i>Rearrangement of fuzzy formal contexts for reducing cost of algorithms</i> Domingo López-Rodríguez, Manuel Ojeda Hernández
	<i>Enhancing JAAD with Knowledge Graphs for Improved Pedestrian Crossing Predictions</i> Sandra Victor, Gowrishankar Ganesh, Madalina Croitoru
	<i>Symbolic Artificial Intelligence for Schema Therapy using Knowledge Graphs</i> Madalina Croitoru, Nathalie Blanc, Royce Anders
11:00–11:20	<b>Coffee break</b>
11:20–13:20	<b>Session 6</b> Chairperson: Ondrej Krídlo
	<i>Semantic explorations in Boolean matrix factorization utilizing formal concepts</i> Radim Belohlavek, Martin Trnecka
	<i>Description Lattices of Generalised Convex Hulls</i> Christophe Demko, Karel Bertet, Jean-François Viaud, Cyril Faucher, Damien Mondou
	<i>Shapley value in classification problems with Triadic Formal Concept Analysis</i> Martin Waffo Kemgne, Blaise Blieriot Koguep Njionou, Leonard Kwuida, Dmitry I. Ignatov
	<i>What is the intrinsic dimension of your binary data? and how to compute it quickly</i> Tom Hanika, Tobias Hille
	<i>Aggregation of fuzzy graphs</i> Francisco Javier Talavera, Carlos Bejines, Sergio Ardanza-Trevijano and Jorge Elorza
	<i>Bimorphisms and attribute implications in heterogeneous formal contexts</i> L'ubomír Antoni, Peter Eliaš, Ján Guniš, Dominika Kotlárová, Stanislav Krajčí, Ondrej Krídlo, Pavol Sokol, L'ubomír Šnajder
13:20–15:00	<b>Lunch</b>

15:00–16:00	<p><b>Round table.</b> Title: Past, present and future of CONCEPTS.  Participants: R. Bělohávek, M. E. Cornejo, B. Ganter, S. Rudolph  Chairperson: Jesús Medina</p>
16:00–18:00	<p><b>Session 7</b>  Chairperson: Sergei Obiedkov</p>
	<p><i>Discovering the Structure of Odorants in Caenorhabditis elegans using Formal Concept Analysis</i>  Emma Reyner-Fuentes, Carmen Peláez-Moreno, Francisco José Valverde-Albacete</p>
	<p><i>Exploiting Formal Concept Analysis for Data Modeling in Data Lakes</i>  Anes Bendimerad, Romain Mathonat, Youcef Remil, Mehdi Kaytoue</p>
	<p><i>Document Classification via Stable Graph Patterns and Conceptual AMR Graphs</i>  Eric George Parakal, Egor Dudyrev, Sergei O. Kuznetsov, Amedeo Napoli</p>
	<p><i>(Kw) Interpretability of Formal Concepts in Word Co-occurrence Matrices</i>  Akihiro Maeda, Takuma Torii and Shohei Hidaka</p>
	<p><i>(Kw) Computing Stable Extensions of Argumentation Frameworks using Formal Concept Analysis</i>  Sergei Obiedkov and Baris Sertkaya</p>
	<p><i>(Kw) On the impact of sup-compositions in the resolution of multi-adjoint relation equations</i>  David Lobo, Víctor López-Marchante, Jesús Medina</p>
20:30	<p><b>Gala dinner</b></p>

<b>FRIDAY 13<sup>th</sup></b>	
<b>Location: Aulario "La Bomba" (Building 1812)</b>	
10:00–11:00	<b>Keynote Speaker - Sebastian Rudolph</b> Title: How to agree to disagree: managing conceptual diversity using standpoint logic. Chairperson: Uta Priss
11:00–11:20	<b>Coffee Break</b>
11:20–13:20	<b>Session 8</b> Chairperson: Carmen Peláez-Moreno
	<i>(Kw) Connecting concept lattices with bonds between L-fuzzy formal contexts by external information</i> Ondrej Krídlo, Domingo López-Rodríguez, Lubomir Antoni, Eliaš, Krajčí, Manuel Ojeda-Aciego
	<i>(Kw) Fuzzy relational Galois connections between fuzzy transitive digraphs</i> Inma P. Cabrera, Pablo Cordero, Emilio Muñoz-Velasco, Manuel Ojeda-Aciego, Bernard de Baets
	<i>(Kw) Representation of Double Boolean Algebra: A Summarization and Ongoing Work</i> Prosenjit Howlader, Churn Jung Liao, and Mohua Banerjee
	<i>(Kw) Concept-forming operators of multi-adjoint concept lattices with hedges</i> M. Eugenia Cornejo, Jesús Medina and Francisco José Ocaña
	<i>(Kw) Polyadic Relational Concept Analysis</i> Alexandre Bazin, Jessie Galasso and Giacomo Kahn
	<i>(Kw) A Formalization of Multi-Label Classification in terms of Lattice Theory and Information Theory: Concerning Datasets</i> Francisco Valverde-Albacete, Carmen Peláez-Moreno
13:20–15:00	<b>Closing Lunch Session</b>

**Key works (Kw)** will have 10 minutes for the presentation of the paper, plus 5 minutes for questions.

The rest of contributions will have 15 minutes for the presentation, plus 5 minutes for questions.



Keynote speech:

## Multi-adjoint Formal Concept Analysis. Theory and Applications

Mar a Eugenia Cornejo Piñero

Universidad de Cádiz, Spain

**Abstract:** Due to the inherent imperfection in real databases the fuzzy extension of formal concept analysis (FCA) was a necessity. Multi-adjoint formal concept analysis, introduced by Medina and Ojeda-Aciego, arose as a fuzzy framework of formal concept analysis focused on introducing a general approach capable of conveniently embed the different fuzzy extensions of concept lattices given in the literature, such as the original framework given by Burusco and Fuentes-González, and the so-called approaches given by Belohlavek, Polandt, Georgescu, Popescu and Krajci. For instance, a general algebraic structure was considered in which the operators could be non-commutative and non-associative, allowing a more flexible modeling of the examples/dataset. Another interesting feature is that it is possible to consider different adjoint triples or pairs with respect to a given triple of posets, which allows to offer the possibility of considering different degrees of preference on the attributes/objects of a database. These preference degrees can be interpreted as the values of a membership function modeling a preference on the attributes and/or objects, following the semantics proposed by Zadeh, in which the values represent the intensity of preference in favor of a specific attribute/object. Attribute reduction and size reduction of the concept lattice, and the computation of reducts are significant challenges in this theory, which is fundamental for detecting redundant information and selecting the most relevant variables in the (real) dataset. Different approaches have been introduced with remarkable results. Attribute implications theory is another fundamental challenge in FCA, where recent advances have also been obtained and they have been applied to real cases with good results. This presentation provides a wide view on multi-adjoint formal concept analysis including theoretical definitions, properties, and important tasks where this theory has successfully been applied, such as the commented above attribute reduction and attribute implications theory. In addition, different applications will be shown.

## Session 1

## Subdirectly irreducible and semisimple double Boolean algebras

Leonard Kwuida<sup>1</sup> and Etienne Romuald Temgoua Alomo<sup>2</sup>

<sup>1</sup> Bern University of Applied Sciences, Business School  
Institut Applied Data Science & Finance Brückenstrasse 73, 3005 Bern  
e-mail: leonard.kwuida@bfh.ch

<sup>2</sup> University of Yaounde I, École Normale Supérieure de Yaoundé  
Department of Mathematics, P.O. Box 47, Yaoundé, Cameroon  
e-mail: retemgoua@gmail.com

**Abstract:** Double Boolean algebras are algebras  $\underline{D} = (D, \cup, \cap, \cdot, \cdot, \cdot, \cdot, \cdot, \cdot)$  of type  $(2, 2, 1, 1, 0, 0)$  introduced by Rudolf Wille to capture the equational theory of protoconcept algebras. A famous theorem of Birkhoff says that any variety is determined by its subdirectly irreducible members. In this work we give a construction that leads to a concrete embedding of double Boolean algebras into the protoconcept algebra. We characterize subdirectly irreducible, simple and semisimple double Boolean algebras.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_1](https://doi.org/10.1007/978-3-031-67868-4_1)

## The Birkhoff completion of finite lattices

Mohammad Abdulla<sup>1, 2</sup>, Johannes Hirth<sup>1,2</sup> and Gerd Stumme<sup>1,2</sup>

<sup>1</sup> Knowledge & Data Engineering Group, University of Kassel, Germany

<sup>2</sup> Interdisciplinary Research Center for Information System Design, University of Kassel, Germany

**Abstract:** We introduce the Birkhoff completion as the smallest distributive lattice in which a given finite lattice can be embedded as semi-lattice. We discuss its relationship to implicational theories, in particular to R. Wille's simply-implicational theories and truncated distributive lattices. By an example, we show how the Birkhoff completion can be used as a tool for ordinal data science.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_2](https://doi.org/10.1007/978-3-031-67868-4_2)

## Arrow relations in lattices of integer partitions

Asma'a Almazaydeha<sup>1</sup>, Mike Behrisch<sup>2</sup>, Edith Vargas-García<sup>3</sup>  
and Andreas Wachtel<sup>3</sup>

<sup>1</sup> Department of Mathematics, Tafila Technical University, PO Box 179, 66110, Tafila, Jordan

<sup>2</sup> Institute of Discrete Mathematics and Geometry, TU Wien, Wiedner Hauptstr. 8–10, 1040, Vienna, Austria

<sup>3</sup> Department of Mathematics, ITAM, Río Hondo 1, Ciudad de México, CP 01080, Mexico

**Abstract:** We give a complete characterisation of the single and double arrow relations of the standard context  $\mathbb{K}(L_n)$  of the lattice  $L_n$  of partitions of any positive integer  $n$  under the dominance order, thereby addressing an open question of Ganter, 2020/2022.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109244>

## Session 2

# Conceptual knowledge modelling for human{AI teaming in data{frugal industrial environments

Vedran Galetic,<sup>1</sup> Dylan Sheldon<sup>1</sup> and Alistair Nottle<sup>1</sup>

<sup>1</sup> Airbus Central R&T, Bristol, United Kingdom.

e-mail: {vedran.galetic,dylan.sheldon,alistair.nottle}@airbus.com

**Abstract:** When AI interacts with humans in complex environments, such as aerospace manufacturing, safety of operation is of paramount importance. Trustworthiness of AI needs to be ensured through, among other things, explainability of its behaviour and rationale, which is typically a challenge for current deep neural network-based systems. We tackle the knowledge comprehensibility aspect of intrinsic explainability by suggesting a concept-level environment awareness model combining various complementary knowledge sources — statistical learning using dedicated property detectors through publicly available software, and crowd-sourced common-sense knowledge graphs. Our approach also addresses the issue of data-frugal learning, typical for environments with highly specific purpose-built artefacts. We adopt Gärdenfors’s Conceptual Spaces as a cognitively-motivated knowledge representation framework and apply our typicality quantification model in a use case on interpretable classification of manufacturing artefacts.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_15](https://doi.org/10.1007/978-3-031-67868-4_15)

# Handling knowledge over moving object trajectories using Formal Concept Analysis

Rouaa Wannous<sup>1</sup>, Salah Eddine Boukhetta<sup>1</sup>, and Cecile Vincent<sup>1</sup>

<sup>1</sup> La Rochelle University, L3i laboratory, EA 2118, France

e-mail: [frouaa.wannous,cecile.vincent@univ-lr.fr](mailto:frouaa.wannous,cecile.vincent@univ-lr.fr)

[boukhattasalaheddine@gmail.com](mailto:boukhattasalaheddine@gmail.com)

**Abstract:** For us, the term semantic trajectories of moving objects corresponds to a sequence of spatio-temporal points with associated semantic information. Spatio-temporal points are directly generated by sensors that capture the position of moving object in time.

In this paper, we work on a marine mammal trajectories case study. In fact, we consider seals' trajectories in order to understand their behavior as groups and identify their activities together at the same time in the same place. We define mobile object's activities in form of rules given by the domain expert. To accomplish knowledge over trajectories, we use the platform GALACTIC, which is a new platform based on Formal Concept Analysis (FCA) for calculating a concept lattice from heterogeneous and complex data. Data in GALACTIC are described by predicates according to their types. Here, we will use interval sequences plugins to analyse seals' trajectories, where interval sequences are represented by a set of time intervals in which a seal perform an activity in a geographical zone. Finally, the results show activities of group of seals simultaneously.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_16](https://doi.org/10.1007/978-3-031-67868-4_16)

## FCAvizIR: Exploring relational data set's implications using metrics and topics

Lola Musslin<sup>1</sup>, Alexandre Bazin<sup>1</sup>, Marianne Huchard<sup>1</sup>, Pierre Martin<sup>2, 3</sup>, Pascal Poncelet<sup>1</sup>, Vincent Raveneau<sup>1</sup> and Arnaud Salaberry<sup>1, 4</sup>

<sup>1</sup>LIRMM, Univ. Montpellier, CNRS, Montpellier, France.

<sup>2</sup>CIRAD, UPR AIDA, F-34398 Montpellier France.

<sup>3</sup>AIDA, Univ. Montpellier, CIRAD, Montpellier, France.

<sup>4</sup>AMIS, Univ. Paul-Valéry Montpellier 3, Montpellier, France.

**Abstract:** Implication is a core notion of Formal Concept Analysis and its extensions. It provides information about the regularities present in the data. When one considers a relational data set of real-size, implications are numerous and their formulation, which combines primitive and relational attributes computed using Relational Concept Analysis framework, is complex. For an expert wishing to answer a question based on such a corpus of implications, having a smart exploration strategy is crucial. In this paper, we propose a visual approach, implemented in a web platform named FCAvizIR, for leveraging such corpus. Comprised of three interactive and coordinated views and a toolbox, FCAvizIR has been designed to explore corpora of implication rules following Schneiderman's famous mantra "overview first, zoom and filter, then details on demand". It enables metrics filtering, e.g. fixing a minimum and a maximum support value, and the multiple selection of relations and attributes in the premise and in the conclusion to identify the corresponding subset of implications presented as a list and Euler diagrams. An example of exploration is presented using an excerpt of Knomana to analyze plant-based extracts for controlling pest.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_10](https://doi.org/10.1007/978-3-031-67868-4_10)

# Realizability of rectangular Euler diagrams

Dominik Dürrschnabel,<sup>1,2</sup> and Uta Priss<sup>3</sup>

<sup>1</sup> Knowledge & Data Engineering Group, University of Kassel, Kassel, Germany

<sup>2</sup> Interdisciplinary Research Center for Information System Design, Kassel, Germany  
e-mail: duerrschnabel@cs.uni-kassel.de

<sup>3</sup> Faculty of Computer Science, Ostfalia University of Applied Sciences, Wolfenbüttel, Germany  
e-mail: u.priss@ostfalia.de

**Abstract:** Euler diagrams are a tool for the graphical representation of set relations. Due to their simple way of visualizing elements in the sets by geometric containment, they are easily readable by an inexperienced reader. Euler diagrams where the sets are visualized as aligned rectangles are of special interest. In this work, we link the existence of such rectangular Euler diagrams to the order dimension of an associated order relation. For this, we consider Euler diagrams in one and two dimensions. In the one-dimensional case, this correspondence provides us with a polynomial-time algorithm to compute the Euler diagrams, while the two-dimensional case is linked to an NP-complete problem which we approach with an exponential-time algorithm.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_11](https://doi.org/10.1007/978-3-031-67868-4_11)



## Spanning concept trees: algorithms and interaction

Tim Pattison

Defence Science & Technology Group West Ave, Edinburgh South Australia 5111  
e-mail: tim.pattison@defence.gov.au

**Abstract:** The Concept Tree is a means of browsing the concept lattice of a formal context using readily-available tools for the interactive visualisation of trees. While respecting the lattice order, the directed Concept Tree includes arcs between concepts which are not mutual covers, and hence is not a spanning tree of the lattice digraph. Such arcs misrepresent the structure of the digraph. This paper surveys and augments options for constructing a Spanning Concept Tree, including: as an auxiliary data structure of existing Formal Concept Analysis algorithms; transitive reduction of the partial order amongst previously-enumerated concepts to produce the lattice digraph, from which a spanning tree is then derived; a novel algorithm which exploits the Reverse Llectic Order (RLO) of intents to construct a spanning tree from the set of formal concepts; and a novel algorithm which identifies and remediates only those arcs in the Concept Tree which are not arcs in the lattice digraph. Both novel algorithms exploit the property that a post-order traversal of the Concept Tree returns the concepts in RLO. They produce Spanning Concept Trees in which the parent of each concept is its first cover in the RLO, and whose children, like those in the Concept Tree, are in RLO. However, some concepts in the Spanning Concept Tree may depart from their canonical positions in the Concept Tree. The implications of this departure for interactive exploration – vice algorithmic traversal – of the Spanning Concept Tree are also explored.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_12](https://doi.org/10.1007/978-3-031-67868-4_12)

# A repository for formal contexts

Tom Hanika<sup>1</sup> and Robert Jaschke<sup>2</sup>

<sup>1</sup> University of Hildesheim. Hildesheim, Germany  
e-mail: tom.hanika@uni-hildesheim.de

<sup>2</sup> Berlin School for Library and Information Science Humboldt-Universität zu Berlin.  
e-mail: : robert.jaschke@hu-berlin.de

**Abstract:** Data is always at the center of the theoretical development and investigation of the applicability of Formal Concept Analysis. It is therefore not surprising that a large number of de facto standard data sets are repeatedly used in scientific articles and software tools. However, this distribution of data sets poses a problem for the sustainable further development of the research field. There is a lack of a centralized location that holds and describes FCA datasets and links already known analysis results. This article analyses the current state of the dissemination of FCA datasets, presents the requirements for a central FCA repository and highlights the challenges for this.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_13](https://doi.org/10.1007/978-3-031-67868-4_13)

**Keynote speech:**

## **Contextual Attribute Logics**

**Bernhard Ganter**

TU Dresden, Germany

**Abstract:** Mathematical formal logic is a comprehensive and profound theory that is valuable and significant also for Formal Concept Analysis. However, it is not to be understood as “concept logic” in the philosophical sense. Its language and technical terms are geared towards its main field of application, mathematics. That is why Rudolf Wille began early on to formulate a logic of formal concepts under the name “Contextual Logic”. A first building block for this is Contextual Attribute Logic. However, the initial publication on this topic remained largely unnoticed because it did not show much that was mathematically new. In fact, a reader could quite rightly say that this attribute logic is merely reformulated Propositional Logic (and more generally that Contextual Logic can be translated into Predicate Logic). However, this very argument was also put forward for years to Formal Concept Analysis itself. The fact that a reformulation, guided by an interpretative goal, and the associated restructuring can release completely new forces, was only understood when Formal Concept Analysis was taken up by the academic world in thousands of scientific publications. A suitably coordinated logical language is part of such a restructuring. In our talk, we will present Contextual Attribute Logic again, going a few steps further than the previously published contributions. As always, our goal is to provide a framework that is suitable for holding together the divergent developments within Formal Concept Analysis and contributes to a more unified theory.

## Session 3

## Exploring the 3-dimensional variability of websites' user-stories using Triadic Concept Analysis

Alexandre Bazin<sup>1</sup>, Thomas Georges<sup>1, 2</sup>, Marianne Huchard<sup>1</sup>, Pierre Martin<sup>3</sup> and Chouki Tibermacine<sup>1</sup>

<sup>1</sup> LIRMM, Univ Montpellier, CNRS, Montpellier, France.

<sup>2</sup> ITK -Predict & Decide, Montpellier, France.

<sup>3</sup>AIDA, Cirad, Montpellier, France

**Abstract:** Configurable software systems and families of similar software systems are increasingly being considered by industry to provide software tailored to each customer's needs. Their development requires managing software variability, i.e. commonalities, differences and constraints. A primary step is properly analyzing the variability of software, which can be done at various levels, from specification to deployment. In this paper, we focus on the software variability expressed through user-stories, viz. short formatted sentences indicating which user role can perform which action at the specification level. At this level, variability is usually analyzed in a two dimension view, i.e. software described by features, and considering the roles apart. The novelty of this work is to model the three dimensions of the variability (i.e. software, roles, features) and explore it using Triadic Concept Analysis (TCA), an extension of Formal Concept Analysis. The variability exploration is based on the extraction of 3- dimensional implication rules. The adopted methodology is applied to a case study made of 65 commercial web sites in four domains, i.e. manga, martial arts sports equipment, board games including trading cards, and video-games. This work highlights the diversity of information provided by such methodology to draw directions for the development of a new product or for building software variability models.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109248>

## Exploring old arabic remedies with Formal and Relational Concept Analysis

Vanessa Fokou<sup>1</sup>, Karim El Ha <sup>1,2</sup>, Agnes Braud<sup>1</sup>, Xavier Dolques<sup>1</sup>, Florence Le Ber<sup>1</sup> and Veronique Pitchon<sup>2</sup>

<sup>1</sup> Université de Strasbourg, ENGEES, CNRS, ICube UMR 7357, F 67000 Strasbourg, France

e-mail: [fvfokou](mailto:fvfokou), [agnes.braud](mailto:agnes.braud), [dolques](mailto:dolques), [florence.le-ber@unistra.fr](mailto:florence.le-ber@unistra.fr)

<sup>2</sup> Université de Strasbourg, CNRS, Archimède UMR 7044, F 67000 Strasbourg, France

e-mail: [pitchon@unistra.fr](mailto:pitchon@unistra.fr), [karim.el-haff@etu.unistra.fr](mailto:karim.el-haff@etu.unistra.fr)

**Abstract:** Exploring old pharamacopeia is a promising way to find active ingredients that can be useful to design new drugs. Nevertheless, studying these texts is a laborious task for biologists. Therefore, an interdisciplinary project was undertaken: texts have been annotated to extract relevant information and represent it within a graph database. Formal Concept Analysis (FCA) and Relational Concept Analysis (RCA) have then been used to explore this database, in order to answer questions regarding remedies and their ingredients. This paper presents the data and some results obtained with FCA and RCA. It highlights the suitability of these approaches to explore these data and answer biologist needs.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_20](https://doi.org/10.1007/978-3-031-67868-4_20)

## Conceptual mapping of controversies

Claude Draude<sup>2,4</sup>, Dominik Dürrschnabel<sup>1,4</sup>, Johannes Hirth<sup>1,4</sup>,  
Viktoria Horn<sup>2,4</sup>, Jonathan Kropf<sup>3,4</sup>, Jörn Lamla<sup>3,4</sup>, Gerd  
Stumme<sup>1,4</sup>, and Markus Uhlmann<sup>3,4</sup>

<sup>1</sup> Knowledge & Data Engineering, University of Kassel, Germany.  
e-mail: [fduerschnabel](mailto:fduerschnabel), [hirth](mailto:hirth), [stumme@cs.uni-kassel.de](mailto:stumme@cs.uni-kassel.de).

<sup>2</sup> Participatory IT Design, University of Kassel, Germany.  
e-mail: [fclaude.draude](mailto:fclaude.draude), [viktoria.horn@uni-kassel.de](mailto:viktoria.horn@uni-kassel.de).

<sup>3</sup> Sociological Theory, University of Kassel, Germany.  
e-mail: [fkropf](mailto:fkropf), [lamla](mailto:lamla), [markus.uhlmann@uni-kassel.de](mailto:markus.uhlmann@uni-kassel.de).

<sup>4</sup> Interdisciplinary Research Center for Information System Design, University of Kassel, Germany.

**Abstract:** With our work, we contribute towards a qualitative analysis of the discourse on controversies in online news media. For this, we employ Formal Concept Analysis and the economics of conventions to derive conceptual controversy maps. In our experiments, we analyze two maps from different news journals with methods from ordinal data science. We show how these methods can be used to assess the diversity, complexity and potential bias of controversies. In addition to that, we discuss how the conceptual diagrams can be used to navigate between news articles.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_14](https://doi.org/10.1007/978-3-031-67868-4_14)

## Session 4

## Towards a generalized modus ponens based on the $\varphi$ -index of inclusion

Carolina Diaz-Montarroso<sup>1</sup>, Nicolas Madrid<sup>1</sup> and Eloisa Ramirez-Poussa<sup>1</sup>

<sup>1</sup> Depto. de Matemáticas. Universidad de Cádiz. Spain.  
e-mail: carolina.diazmontarroso@alum.uca.es, nicolas.madrid@uca.es,  
eloisa.ramirez@uca.es

**Abstract:** This paper proposes a generalized modus ponens and a generalized modus tollens based on the  $\varphi$ -index of inclusion. Moreover, we analyze the properties of generalized modus ponens and generalized modus tollens according to the axioms proposed by Baldwin and Pilsworth.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_3](https://doi.org/10.1007/978-3-031-67868-4_3)

## Efficiency of fuzzy decision algorithms based on the strength of decision rules

Fernando Chacon-Gomez<sup>1</sup>, María Eugenia Cornejo Piñero<sup>1</sup>,  
Jesus Medina<sup>1</sup>

<sup>1</sup> Depto. de Matemáticas. Universidad de Cádiz. Spain.

e-mail: fernando.chacon,mariaeugenia.cornejo,jesus.medina@uca.es

**Abstract:** Characterizing data sets through logic rules is a fundamental task for modeling knowledge systems. Mathematical tools, such as Rough Set Theory (RST) and Formal Concept Analysis (FCA), offer mechanisms for automatically obtaining these logic rules. In this paper, we will analyse a special kind of set of logic rules in fuzzy rough set theory called decision algorithm. In particular, a definition of efficiency of a decision algorithm is introduced taking into account a new fuzzy relevance indicator based on the strength of the decision rules.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_4](https://doi.org/10.1007/978-3-031-67868-4_4)



# Comparing Relational Concept Analysis and Graph-FCA on their common ground

Vanessa Fokou<sup>1</sup>, Peggy Cellier<sup>2</sup>, Xavier Dolques<sup>1</sup>, Sebastien Ferre<sup>2</sup> and Florence Le Ber<sup>1</sup>

<sup>1</sup> Université de Strasbourg, ENGEES, CNRS, ICube UMR 7357, F 67000 Strasbourg, France.

e-mail: [fvfokou](mailto:fvfokou), [dolquesg@unistra.fr](mailto:dolquesg@unistra.fr), [florence.leber@engees.unistra.fr](mailto:florence.leber@engees.unistra.fr).

<sup>2</sup> Univ Rennes, CNRS, Inria, IRISA - UMR 6074, Rennes, France.

e-mail: [fpeggy.cellier](mailto:fpeggy.cellier), [Sebastien.Ferre@irisa.fr](mailto:Sebastien.Ferre@irisa.fr).

**Abstract:** Relational Concept Analysis (RCA) and Graph-FCA (GCA) have been defined as Formal Concepts Analysis (FCA) extensions for processing relational data and knowledge graphs respectively. Nevertheless, whereas their purposes seem similar, and their results may appear to be identical, the data modeling and the definition and subsumption of concepts are different. In this paper, we compare these two approaches on a common basis, considering only unary and binary relations for GCA and the existential quantifier for RCA. We focus on examples showing the similarities and dissimilarities between the two methods, and highlighting how cycles are processed differently by RCA and GCA.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_5](https://doi.org/10.1007/978-3-031-67868-4_5)

# What can FCA-based Boolean matrix factorization do for object-attribute biclustering?

Martin Trnečka<sup>1</sup> and Roman Vyjidacek<sup>1</sup>

<sup>1</sup> Dept. Computer Science, Palacký University Olomouc, Olomouc, Czech Republic  
e-mail: martin.trnecka@gmail.com, roman.vyjidacek@upol.cz

**Abstract:** We introduce preliminary results from an ongoing study on FCA-based Boolean Matrix Factorization (BMF) and its application in object-attribute biclusters enumeration. Namely, we show that standard methods may overlook some object-attribute biclusters, and we propose a novel factor extension approach that can add some of the overlooked biclusters. The presented method computes biclusters employing logic similar to that of standard methods. Additionally, we outline the utilization of a well-known technique used in BMF and present topics for future research.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_9](https://doi.org/10.1007/978-3-031-67868-4_9)

## Analyzing the relationship between the factorization of formal contexts and independent subcontexts

Roberto G. Aragon<sup>1</sup>, Jesus Medina<sup>1</sup> and Eloisa Ramirez-Poussa<sup>1</sup>

<sup>1</sup> Depto. de Matemáticas. Universidad de Cádiz. Spain.  
e-mail: [rroberto.aragon,jesus.medina,eloisa.ramirezg@uca.es](mailto:rroberto.aragon,jesus.medina,eloisa.ramirezg@uca.es)

**Abstract:** This is a keywork of the paper: R. G. Aragón, J. Medina, and E. Ramírez-Poussa. *Factorizing formal contexts from closures of necessity operators*. *Comp. Appl. Math*, 43(124), 2024.

**DOI:** <https://doi.org/10.1007/s40314-024-02590-0>

**Keynote speech:**

## **Interactions between the psychology of concepts and conceptual exploration of data**

**Radim Belohlavek**

Department of Computer Science, Palacký University Olomouc, Czech Republic

**Abstract:** Both the psychology of concepts and conceptual exploration of data have developed a rich body of knowledge (repertoire of theories and tools). Naturally, these two areas have different aims. We argue that despite their focus on different phenomena, proper interactions between the psychology of concepts and conceptual exploration of data may benefit both areas. For this purpose, we provide examples of recent work involving human categorization, typicality, similarity, and factor analysis.

## Session 5

## Rearrangement of fuzzy formal contexts for reducing cost of algorithms

Domingo Lopez-Rodríguez,<sup>1</sup> and Manuel Ojeda-Hernández<sup>1</sup>

<sup>1</sup> Depto. de Matemática Aplicada, Universidad de Málaga, Málaga, Spain  
e-mail: [fdominlopez,manuojeda@uma.es](mailto:fdominlopez,manuojeda@uma.es)

**Abstract:** The influence of attribute ordering on the runtime efficiency of FCA algorithms has long been a subject of conjecture, yet no prior published work has directly addressed this issue. This paper proposes a novel approach, introducing criteria for ranking attribute importance within an  $L$ -fuzzy formal context. The primary objective is to reduce the runtime of concept lattice construction algorithms by strategically reordering attributes based on these criteria.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_8](https://doi.org/10.1007/978-3-031-67868-4_8)

# Enhancing JAAD with knowledge graphs for improved pedestrian crossing predictions

Sandra Victor<sup>1</sup>, Gowrishankar Ganesh<sup>1</sup> and Madalina Croitoru<sup>1</sup>

<sup>1</sup> LIRMM, CNRS and University of Montpellier, Montpellier, France  
e-mail: [fsvictor,gowrishankar,croitorug@lirmm.fr](mailto:fsvictor,gowrishankar,croitorug@lirmm.fr)

**Abstract:** In this paper we place ourselves in the broad context of autonomous driving and, more precisely, in the context of road crossing decisions by pedestrians. Machine learning models built by the existing work need as training data datasets constructed by semi-automatic annotation of video images. JAAD (Joint Attention in Autonomous Driving) is a popular behavior annotated dataset in this regard. Our contribution is to provide a knowledge graph based proposal of additional features that are important but missing in JAAD dataset in the context of road crossing decisions by pedestrians.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_21](https://doi.org/10.1007/978-3-031-67868-4_21)

# Symbolic artificial intelligence for schema therapy using knowledge graphs

Madalina Croitoru<sup>1,2</sup>, Nathalie Blanc<sup>2</sup>, and Royce Anders<sup>2</sup>

<sup>1</sup> LIRMM, CNRS, and University of Montpellier, Montpellier, France.  
e-mail: croitoru@lirmm.fr

<sup>2</sup> EPSYLON Laboratory and University Paul-Valéry, Montpellier, France

**Abstract:** In this paper we place ourselves in the broader context of Artificial Intelligence (AI) powered mental health apps and, more precisely, in the context of semi-automated schema based therapy. Our contribution is two fold. First we provide the first rule based ontology in the literature for Schema Therapy and demonstrate how it can be practically used by mental health professionals in supporting their clients. Second we pave the way for explainable, symbolic based AI approaches in mental health that are yet to be investigated alongside the more prominent approaches (currently in fashion) based on large language models (LLMs).

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_22](https://doi.org/10.1007/978-3-031-67868-4_22)

## Session 6

## Semantic explorations in factorizing Boolean data via formal concepts

Radim Belohlavek<sup>1</sup> and Martin Trnečka<sup>1</sup>

<sup>1</sup> Department of Computer Science, Palacký University Olomouc, Czech Republic

**Abstract:** We use now available psychological data involving human concepts, objects covered by these concepts, and binary attributes describing the objects to explore selected semantic aspects of Boolean matrix factorization. Our basic perspective derives from the intuitive requirement that the factors computed from data should represent natural categories latently present in the data. This idea is examined for factorization algorithms that utilize formal concepts to build factors. We provide several experimental observations which imply that the inspected factorization methods deliver semantically sound factors that resemble significant human concepts of the examined domains.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109247>



## Description lattices of generalised convex hulls

Christophe Demko<sup>1</sup>, Karell Bertet<sup>1</sup>, Jean-Francois Viaud<sup>1</sup>, Cyril Faucher<sup>1</sup> and Damien Mondou<sup>1</sup>

<sup>1</sup> L3i, University of La Rochelle, Avenue Michel Crépeau, La Rochelle Cedex 1, 17042, France.

**Abstract:** In this article, we present a new approach to tackle lattice generation for complex and heterogeneous data using the concept of convexity. This is a work that we have already carried out, albeit intuitively, where we proposed the NextPriorityConcept algorithm for generating a meet-semilattice of concepts based on suitable descriptions and strategies. Now, we revisit the essential properties of our description spaces using a stronger formalism based on the properties of closure operators.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109269>

## Shapley value in classification problems with Triadic Formal Concept Analysis

Martin Waffo Kemgne<sup>1</sup>, Blaise Bleriot Koguep Njionou<sup>2</sup>, Leonard Kwuida<sup>3</sup> and Dmitry I. Ignatov.<sup>4</sup>

<sup>1</sup> La Rochelle Université, La Rochelle, France.  
e-mail: martin.waffo.kemgne@univ-lr.fr

<sup>2</sup> University of Dschang, Dschang, Cameroon.

<sup>3</sup> Bern University of Applied Sciences, Bern, Switzerland.  
e-mail: leonard.kwuida@bfh.ch

<sup>4</sup> HSE University, Moscow, Russia  
e-mail: dignatov@hse.ru

**Abstract:** The JSM-method is a supervised classification method, widely used in machine learning. It has recently been used in Triadic Concept Analysis to classify objects. In this paper, we show how Shapley value of a cooperative game with transferable utilities, can be used to give the importance or individual contribution of each attribute-condition pair of a particular object, for its classification to a particular class.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_6](https://doi.org/10.1007/978-3-031-67868-4_6)

# What is the intrinsic dimension of your binary data? { and how to compute it quickly

Tom Hanika<sup>1</sup>, Tobias Hille<sup>2,3</sup>

<sup>1</sup> Intelligent Information Systems, University of Hildesheim, Hildesheim, Germany.  
e-mail: tom.hanika@uni-hildesheim.de

<sup>2</sup> Knowledge & Data Engineering Group, University of Kassel, Kassel, Germany.  
e-mail: hille@cs.uni-kassel.de

<sup>3</sup> Interdisciplinary Research Center for Information System Design, University of Kassel, Kassel, Germany

**Abstract:** Dimensionality is an important aspect for analyzing and understanding (high-dimensional) data. In their 2006 ICDM paper Tatti et al. answered the question for a (interpretable) dimension of binary data tables by introducing a normalized fractal dimension. In the present work we revisit their results and contrast them with a concept based notion of intrinsic dimension (ID) recently introduced for geometric data sets. To do this, we present a novel approximation technique for this ID that is based on computing concepts only up to a certain support value. We demonstrate and evaluate our approximation using all still available datasets from Tatti et al., which have between 469 and 41271 extrinsic dimensions. (Source code and more figures are available at <https://codeberg.org/thille/bd-gid>).

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_7](https://doi.org/10.1007/978-3-031-67868-4_7)

## Aggregation of fuzzy graphs

Francisco Javier Talavera<sup>1, 2</sup>, Carlos Bejines<sup>2</sup>, Sergio Ardanza-Trevijano<sup>1,2</sup> and Jorge Elorza<sup>1, 2</sup>

<sup>1</sup> Universidad de Navarra, Departamento de Física y Matemática Aplicada, Facultad de Ciencias, C. Irunlarrea 1, 31008, Pamplona, Spain.

<sup>2</sup> Instituto de Ciencia de Datos e Inteligencia Artificial, Universidad de Navarra, Spain.

<sup>3</sup> Univesidad de Málaga, Andalucía Tech, 29071, Málaga, Spain.

**Abstract:** Abstract: Our study is centered on the aggregation of fuzzy graphs, looking for conditions under which the aggregation process yields another fuzzy graph. We conduct an in-depth analysis of the preservation of several important properties and structures inherent to fuzzy graphs, like paths, cycles, or bridges. In addition we obtain appropriate criteria for when the aggregation of complete fuzzy graphs is again a complete fuzzy graph.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109243>

## Bimorphisms and attribute implications in heterogeneous formal contexts

L'ubom r Antoni<sup>1</sup>, Peter Elias<sup>2</sup>, Jan Gunis<sup>1</sup>, Dominika Kotlarova<sup>1</sup>, Stanislav Krajci<sup>1</sup>, Ondrej Kr dlo<sup>1</sup>, Pavol Sokol<sup>1</sup> and L'ubom r Snajder

<sup>1</sup> Institute of Computer Science, Faculty of Science, Pavol Jozef Šafárik University in Košice, Jesenná 5, Košice, 04001, Slovak Republic.

<sup>2</sup> Mathematical Institute, Slovak Academy of Sciences, Grešáková 6, Košice, 04001, Slovak Republic.

**Abstract:** Formal concept analysis is a powerful mathematical framework based on mathematical logic and lattice theory for analyzing object-attribute relational systems. Over the decades, Formal concept analysis has evolved from its theoretical foundations into a versatile methodology applied across various disciplines. A heterogeneous formal context provides a feasible generalization of a formal context, enabling diverse truth-degrees of objects, attributes, and fuzzy relations. In our paper, we present extended theoretical results on heterogeneous formal contexts, including bimorphisms, Galois connections, and heterogeneous attribute implications. We recall the basic notions and properties of the heterogeneous formal context and its concept lattice. Moreover, we present extended results on bimorphisms and Galois connections in a heterogeneous formal context, including a self-contained proof of the main result. We include examples of introduced notions in heterogeneous formal contexts and two-valued logic. We propose the extension of attribute implications for heterogeneous formal contexts and explore their validity. By embracing heterogeneity in Formal concept analysis, we enrich its extended theoretical foundations and pave the way for innovative applications across diverse domains, including personal data protection and cybersecurity.

**DOI:** <https://doi.org/10.1016/j.ijar.2024.109245>

## Session 7

## Discovering the structure of odorants in *Caenorhabditis elegans* using Formal Concept Analysis

Emma Reyner-Fuentes<sup>1,2</sup>, Carmen Pelaez-Moreno<sup>2</sup> and Francisco Jose Valverde-Albacete<sup>1</sup>

<sup>1</sup> Depto. Teoría de Señal y Comunicaciones y Sistemas Telemáticos y Computación, Univ. Rey Juan Carlos, Madrid, Spain.

e-mail: femma.reyner,francisco.valverde@urjc.es

<sup>2</sup> Depto. Teoría de Señal y Comunicaciones, Univ. Carlos III de Madrid, Madrid, Spain.

e-mail: ferfuentes, carmen@tscg.uc3m.es

**Abstract:** Embodied and Embedded cognition posits that animals act by operating a sensory-motor loop over an environment through the concurrence of their nervous systems. A notable challenge in studying the nervous system lies in the absence of a model of its sensorium, the mechanism whereby an organism perceives its surroundings. This paper addresses the inquiry into the perception mechanisms of *Caenorhabditis elegans* as a model organism. To this end, we have delimited the perceptual domain to 23 distinct odorants, for which we have the corresponding neural activity data from the 11 pairs of sensory neurons. This paper elucidates how the integration of various FCA-related methodologies—specifically, K-FCA max-plus and min-plus analyses, as well as cosine distance calculations—allows for the obtention of a representation of the perceptual framework of *C. elegans*. Additionally, we propose avenues for further refinement, including the consideration of the idempotent singular value decomposition within the FCA framework to improve said perceptual representations.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_17](https://doi.org/10.1007/978-3-031-67868-4_17)

# Exploiting Formal Concept Analysis for data modeling in data lakes

Anes Bendimerad<sup>1</sup>, Romain Mathonat<sup>1</sup>, Youcef Remil<sup>1</sup> and Mehdi Kaytoue<sup>1</sup>

<sup>1</sup> Infologic R&D, 26500 Bourg-Lés-Valence, France  
e-mail: mka@infologic.fr

**Abstract:** Data lakes are widely used to store extensive and heterogeneous datasets for advanced analytics. However, the unstructured nature of data in these repositories introduces complexities in exploiting them and extracting meaningful insights. This motivates the need of exploring efficient approaches for consolidating data lakes and deriving a common and unified schema. This paper introduces a practical data visualization and analysis approach rooted in Formal Concept Analysis (FCA) to systematically clean, organize, and design data structures within a data lake. We explore diverse data structures stored in our data lake at Infologic, including InfluxDB measurements and Elasticsearch indexes, aiming to derive conventions for a more accessible data model. Leveraging FCA, we represent data structures as objects, analyze the concept lattice, and present two strategies—top-down and bottom-up—to unify these structures and establish a common schema. Our methodology yields significant results, enabling the identification of common concepts in the data structures, such as “resources” along with their underlying shared fields (timestamp, type, usedRatio, etc.). Moreover, the number of distinct data structure field names is reduced by 54% (from 190 to 88) in the studied subset of our data lake. We achieve a complete coverage of 80% of data structures with only 34 distinct field names, a significant improvement from the initial 121 field names that were needed to reach such coverage. The paper provides insights into the Infologic ecosystem, problem formulation, exploration strategies, and presents both qualitative and quantitative results. The source code and datasets of this work are made available: <https://zenodo.org/records/10589722>

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_18](https://doi.org/10.1007/978-3-031-67868-4_18)

# Document classification via stable graph patterns and conceptual AMR graphs

Eric George Parakal<sup>1</sup>, Egor Dudyrev<sup>1,2</sup>, Sergei O. Kuznetsov<sup>1</sup>,  
Amedeo Napoli<sup>2</sup>

<sup>1</sup> National Research University Higher School of Economics, Pokrovsky Blvd, 11, Moscow, 109028, Russia.

e-mail: [feparakal,skuznetsov@hse.ru](mailto:feparakal,skuznetsov@hse.ru)

<sup>2</sup> Université de Lorraine, CNRS, LORIA, 54000 Nancy, France.

e-mail: [fegor.dudyrev,amedeo.napoli@loria.fr](mailto:fegor.dudyrev,amedeo.napoli@loria.fr)

**Abstract:** This paper proposes an approach and an associated system based on pattern structures, aimed at the classification of documents represented as graphs. The representation of documents relies on Abstract Meaning Representation (AMR) document graphs. Given a set of AMR document graphs, the system learns characteristic graph patterns, that can be reused by an aggregate rule classifier to predict the class of a document. The selection of the most stable graph patterns is based on the gSOFIA algorithm and the  $\Delta$ -stability measure. In the experiments, two document datasets are considered for validating the approach. The first includes documents belonging to 10 different newsgroups and the second contains sports news articles belonging to 5 topical areas. The results in terms of the macro-averaged F1 scores, are quite satisfactory and show that the approach is well-founded and useful.

**DOI:** [https://doi.org/10.1007/978-3-031-67868-4\\_19](https://doi.org/10.1007/978-3-031-67868-4_19)



## Interpretability of formal concepts in word co-occurrence matrices

Akihiro Maeda<sup>1</sup>, Takuma Torii<sup>2</sup> and Shohei Hidaka<sup>1</sup>

<sup>1</sup>Japan Advanced Institute of Science and Technology, Ishikawa, Japan  
e-mail: [fakihiro.maeda,shhidaka@jaist.ac.jp](mailto:fakihiro.maeda,shhidaka@jaist.ac.jp)

<sup>2</sup>Tokyo Denki University, Saitama, Japan  
e-mail: [tak.torii@mail.dendai.ac.jp](mailto:tak.torii@mail.dendai.ac.jp)

**Abstract:** This study addresses the interpretability of word representations through an investigation of a word co-occurrence matrix. Employing Formal Concept Analysis, we aimed to reveal an underlying structure that is consistent with human interpretation. We unveil the emergence of hierarchical and geometrical structures within word vectors. We show that the identified formal concepts align with interpretable categories.

Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL 2024): <https://aclanthology.org/2024.findings-acl.278>

# Computing stable extensions of argumentation frameworks using Formal Concept Analysis

Sergei Obiedkov<sup>1</sup> and Baris Sertkaya<sup>2</sup>

<sup>1</sup> Knowledge-Based Systems Group, Faculty of Computer Science TU Dresden  
Germany.

e-mail: sergei.obiedkov@tu-dresden.de

<sup>2</sup> Frankfurt University of Applied Sciences, Germany.

e-mail: sertkaya@fb2.fra-uas.de

**Abstract:** We propose an approach based on Formal Concept Analysis (FCA) for computing stable extensions of Abstract Argumentation Frameworks (AFs). To this purpose, we represent an AF as a formal context in which stable extensions of the AF are closed sets called concept intents. We make use of algorithms developed in FCA for computing concept intents in order to compute stable extensions of AFs. Experimental results show that, on AFs with a high density of the attack relation, our algorithms perform significantly better than the existing approaches. The algorithms can be modified to compute other types of extensions, in particular, preferred extensions.

**DOI:** [https://doi.org/10.1007/978-3-031-43619-2\\_13](https://doi.org/10.1007/978-3-031-43619-2_13)

## On the impact of sup-compositions in the resolution of multi-adjoint relation equations

David Lobo<sup>1</sup>, Víctor Lopez-Marchante<sup>1</sup>, Jesús Medina<sup>1</sup>

<sup>1</sup>Depto. de Matemáticas. Universidad de Cádiz. Spain.

e-mail: [fdavid.lobo](mailto:fdavid.lobo), [victor.lopez](mailto:victor.lopez), [jesus.medina@uca.es](mailto:jesus.medina@uca.es)

**Abstract:** Keywork of paper *On the impact of sup-compositions in the resolution of multi-adjoint relation equations* *Mathematical Methods in the Applied Sciences*, 2023, 46, 15581-15598”.

**DOI:** <https://doi.org/10.1002/mma.9414>

**Keynote speech:**

## **How to agree to disagree: managing conceptual diversity using standpoint logic**

**Sebastian Rudolph**

TU Dresden, Germany

**Abstract:** The importance of taking individual, potentially conflicting perspectives into account when dealing with knowledge has been widely recognised. Many existing ontology management approaches fully merge knowledge perspectives, which may require weakening in order to maintain consistency; others represent the distinct views in an entirely detached way. This talk presents an alternative, referred to as Standpoint Logic, a simple, yet versatile multi-modal logic “add-on” for existing KR languages intended for the integrated representation of domain knowledge relative to diverse standpoints, which can be hierarchically organised, combined, and put in relation with each other. Starting from the generic framework of First-Order Standpoint Logic (FOSL), we first present the fragment of so-called sentential formulas, for which we provide a polytime translation into the standpoint-free version. This result yields decidability and favourable complexities for several decidable fragments of first-order logic, including the very expressive description logic SROIQbs underlying the OWL 2 DL ontology language. By virtue of this, existing highly optimised OWL reasoners can be used to provide practical reasoning support for ontology languages extended by standpoint modelling. Shifting our focus to tractable lightweight formalisms of enhanced scalability, we present Standpoint EL+, a standpoint extension of the popular description logic EL. Satisfiability in this logic can be checked in polynomial time thanks to a satisfiability-checking deduction calculus that allows for a implementation by means of elementary logic programming.

## Session S8

## Connecting concept lattices with bonds between $L$ -fuzzy formal contexts by external information

Ondrej Krídlo<sup>1</sup>, Domingo Lopez-Rodríguez<sup>2</sup>, Ľubomír Antoni<sup>1</sup>, Peter Elias<sup>3</sup>, Stanislav Krajčí<sup>1</sup>, and Manuel Ojeda-Aciego<sup>2</sup>

<sup>1</sup> Institute of Computer Science, Faculty of Science, Pavol Jozef Šafárik University in Košice, Jesenná 5, Košice, 04001, Slovak Republic.

e-mail: [ondrej.kridlo](mailto:ondrej.kridlo@upjs.sk), [lubomir.antoni](mailto:lubomir.antoni@upjs.sk), [stanislav.krajci](mailto:stanislav.krajci@upjs.sk)

<sup>2</sup> Depto. de Matemática Aplicada, Universidad de Málaga, Málaga, Spain.

e-mail: [fdominlopez](mailto:fdominlopez@uma.es), [aciego](mailto:aciego@uma.es)

<sup>3</sup> Mathematical Institute, Slovak Academy of Sciences, Grešákova 6, 040 01, Košice, Slovak Republic.

e-mail: [elias@saske.sk](mailto:elias@saske.sk)

**Abstract:** We have delved into the interpretation of two novel methods for selecting appropriate bonds between  $L$ -fuzzy formal contexts, based on the use of the rigorous and benevolent concept-forming operators. The strategy presented therein for the construction of the rigorous and the benevolent bonds is knowledge-driven: the presence of external information about the strength of the connection about the attribute sets, given by operator  $p: A_1 \times A_2 \rightarrow L$ , induces both types of bond. Therefore, these new methods overcome the difficulty of bond interpretation by taking advantage of the incorporation of knowledge into the problem. In that paper, we formally verified that the bonds built using this strategy produce results coherent with the piece of external information used.

**DOI:** <https://doi.org/10.1016/j.ins.2023.119498>

## Fuzzy relational Galois connections between fuzzy transitive digraphs

Inma P. Cabrera<sup>1</sup>, Pablo Cordero<sup>1</sup>, Emilio Muñoz-Velasco<sup>1</sup>,  
Manuel Ojeda-Aciego<sup>1</sup> and Bernard de Baets.<sup>2</sup>

<sup>1</sup> Depto. Matemática Aplicada, Universidad de Málaga, Andalucía Tech, Spain  
e-mail: [ipcabrera](mailto:ipcabrera@uma.es), [pcordero](mailto:pcordero@uma.es), [ejmuno](mailto:ejmuno@uma.es), [aciegog](mailto:aciegog@uma.es)

<sup>2</sup> Data Analysis and Mathematical Modelling, Ghent University, Belgium.  
e-mail: [Bernard.DeBaets@UGent.be](mailto:Bernard.DeBaets@UGent.be)

**Abstract:** We present a fuzzy version of the notion of relational Galois connection between fuzzy transitive directed graphs (fuzzy T-digraphs) on the specific setting in which the underlying algebra of truth values is a complete Heyting algebra. The components of such fuzzy Galois connection are fuzzy relations satisfying certain reasonable properties expressed in terms of the so-called full powering. Moreover, we provide a necessary and sufficient condition under which it is possible to construct a right adjoint for a given fuzzy relation between a fuzzy T-digraph and an unstructured set.

**DOI:** <https://doi.org/10.1016/j.fss.2022.12.012>

## Representation of double Boolean algebra: a summarization and ongoing work

Prosenjit Howlader<sup>1</sup>, Churn Jung Liao<sup>1</sup> and Mohua Banerjee<sup>2</sup>

<sup>1</sup> Institute of Information Science, Academia Sinica, Taipei, 115, Taiwan  
e-mail: [fprosen,liaucj@mail.iis.sinica.edu.tw](mailto:fprosen,liaucj@mail.iis.sinica.edu.tw)

<sup>2</sup> Department of Mathematics and Statistics, Indian Institute of Technology Kanpur, India.  
e-mail: [mohua@iitk.ac.in](mailto:mohua@iitk.ac.in)

**Abstract:** In the line of, Wille (2000), Balbiani (2012) and Vormbrock (2005), in this abstract, we present results on the topological representation of dBa based on Howlader and Banerjee (2023), and our ongoing work on its algebraic representation.

**DOI:** <https://doi.org/10.1007/s00012-023-00811-x>

# Concept-forming operators of multi-adjoint concept lattices with hedges

Mar a Eugenia Cornejo Piñero<sup>1</sup>, Jesus Medina<sup>1</sup> and Francisco Jose Ocana<sup>1</sup>

<sup>1</sup> Depto. de Matemáticas. Universidad de Cádiz. Spain.

e-mail: [fmariaeugenia.cornejo](mailto:fmariaeugenia.cornejo), [jesus.medina](mailto:jesus.medina), [franciscojose.ocana@uca.es](mailto:franciscojose.ocana@uca.es)

**Abstract:** Formal Concept Analysis is an appealing research topic both from a theoretical and applied perspective. Since its introduction in the eighties, different fuzzy generalizations have been proposed in order to deal with the imprecise and vague information contained in databases. Specifically, multi-adjoint concept lattices arise as a general and flexible approach capable of conveniently embed different fuzzy extensions of concept lattices mentioned above. Attribute classification, size lattice reduction, reduct computation and attribute implications are important tasks which have been successfully addressed in the multi-adjoint paradigm.

This work studies the inclusion of truth-stressing hedges in multi-adjoint concept lattices. The formal definition of concept-forming operators of multi-adjoint concept lattices with hedges and its properties are presented. In addition, an isomorphism between a multi-adjoint concept lattice and the concept lattice enriched with truth-stressing hedges is obtained from the new operators.

**DOI:** <https://doi.org/10.1016/j.fss.2023.108854>



# Polyadic Relational Concept Analysis

Alexandre Bazin<sup>1</sup>, Jessie Galasso<sup>2</sup> and Giacomo Kahn<sup>3</sup>

<sup>1</sup>LIRMM, CNRS, Université de Montpellier, France.  
e-mail: alexandre.bazin@umontpellier.fr.

<sup>2</sup>McGill University, Canada.  
e-mail: jessie.galasso-carbonnel@mcgill.ca

<sup>3</sup> Université Lumière Lyon 2, INSA Lyon, Université Claude Bernard Lyon 1, Université Jean Monnet Saint-Etienne, DISP UR4570, 69007 Bron, France.  
e-mail: giacomo.kahn@univ-lyon2.fr

**Abstract:** Formal concept analysis is a mathematical framework based on lattice theory that aims at representing the information contained in binary object-attribute datasets (called formal contexts) in the form of a lattice of so-called formal concepts. Since its introduction, it has been extended to more complex types of data. In this paper, we are interested in two of those extensions: relational concept analysis and polyadic concept analysis that allow to process, respectively, relational data and  $n$ -ary relations. We present a framework for polyadic relational concept analysis that extends relational concept analysis to relational datasets that are made of  $n$ -ary relations. We show its basic properties and that it is a valid extension of relational concept analysis.

**DOI:** <https://doi.org/10.1016/j.ijar.2023.109067>

# A formalization of multi-label classification in terms of Lattice Theory and Information Theory: concerning datasets

Francisco Jose Valverde-Albacete<sup>1</sup>, Carmen Pelaez-Moreno<sup>2</sup>

<sup>1</sup> Depto. Teoría de Señal y Comunicaciones y Sistemas Telemáticos y Computación, Univ. Rey Juan Carlos, Madrid, Spain.  
e-mail: francisco.valverde@urjc.es

<sup>2</sup> Depto. Teoría de Señal y Comunicaciones, Univ. Carlos III de Madrid, Madrid, Spain.  
e-mail: carmen@tsc.uc3m.es

**Abstract:** Multi-label classification (MLC) is a relatively recently-formalized task in Machine Learning. We have proven that this establishes a metaphor of MLC as an information communication channel, using information triangles to quantify information and concept lattices to qualify it.

**DOI:** <https://doi.org/10.3390/math12020346>

# Author Index

- Abdulla, Mohammad, 3  
Almazaydeha, Asma'a, 4  
Anders, Royce, 23  
Antoni, L'ubom r, 29, 37  
Aragon, Roberto G., 19  
Ardanza-Trevijano, Sergio, 28
- Belohlavek, Radim, 20, 24  
Banerjee, Mohua, 39  
Bazin, Alexandre, 7, 12, 41  
Behrischb, Mike, 4  
Bejines, Carlos, 28  
Bendimerad, Anes, 31  
Bertet, Karell, 25  
Blanc, Nathalie, 23  
Boukhetta, Salah Eddine, 6  
Braud, Agnes, 13
- Cabrera, Inma P., 38  
Cellier, Peggy, 17  
Chacon-Gomez, Fernando, 16  
Cordero, Pablo, 38  
Cornejo Piñero, María Eugenia, 1, 16, 40  
Croitoru, Madalina, 22, 23
- Daz-Montarroso, Carolina, 15  
de Baets, Bernard, 38  
Demko, Christophe, 25  
Dolques, Xavier, 13, 17  
Draude, Claude, 14  
Dudyrev, Egor, 32  
Derrschnabel, Dominik, 8, 14
- El Ha , Karim, 13  
Elias, Peter, 29, 37  
Elorza, Jorge, 28
- Faucher, Cyril, 25
- Ferre, Sebastien, 17  
Fokou, Vanessa, 13, 17
- Galasso, Jessie, 41  
Galetic, Vedran, 5  
Ganesh, Gowrishankar, 22  
Ganter, Bernhard, 11  
Georges, Thomas , 12  
Gunis, Jan, 29
- Hanika, Tom, 10, 27  
Hidaka, Shohei, 33  
Hille, Tobias, 27  
Hirth, Johannes, 3, 14  
Horn, Viktoria, 14  
Howlader, Prosenjit, 39  
Huchard, Marianne, 7, 12
- Ignatov, Dmitry I., 26
- Jäschke, Robert, 10
- Kahn, Giacomo, 41  
Kaytoue, Mehdi, 31  
Kemgne, Martin Walo, 26  
Koguep Njionou, Blaise Bleriot, 26  
Kotlarova, Dominika, 29  
Krdlo, Ondrej, 29, 37  
Krajci, Stanislav, 29, 37  
Kropf, Jonathan, 14  
Kuznetsov, Sergei O., 32  
Kwuida, Leonard, 2, 26
- Lopez-Marchante, Victor, 35  
Lopez-Rodríguez, Domingo, 21, 37  
Lamla, Jörn, 14  
Le Ber, Florence, 13, 17  
Liau, Churn Jung, 39  
Lobo, David, 35

- Madrid, Nicolas, 15  
Maeda, Akihiro, 33  
Martin, Pierre, 7, 12  
Mathonat, Romain, 31  
Medina, Jesus, 16, 19, 35, 40  
Mondou, Damien, 25  
Musslin, Lola, 7  
Muñoz-Velasco, Emilio, 38
- Napoli, Amedeo, 32  
Nottle, Alistair, 5
- Obiedkov, Sergei, 34  
Ocana, Francisco Jose, 40  
Ojeda-Aciego, Manuel, 37, 38  
Ojeda-Hernandez, Manuel, 21
- Parakal, Eric George, 32  
Pattison, Tim, 9  
Pelaez-Moreno, Carmen, 30, 42  
Pitchon, Veronique, 13  
Poncelet, Pascal, 7  
Priss, Uta, 8
- Ram rez-Poussa, Elo sa, 15, 19  
Raveneau, Vincent, 7  
Remil, Youcef, 31
- Reyner-Fuentes, Emma, 30  
Rudolph, Sebastian, 36
- Sallaberry, Arnaud, 7  
Sertkaya, Baris, 34  
Sheldon, Dylan, 5  
Snajder, L'ubom r, 29  
Sokol, Pavol, 29  
Stumme, Gerd, 3, 14
- Talavera, Francisco Javier, 28  
Temgoua Alomo, Etienne Romuald, 2  
Tibermacine, Chouki, 12  
Torii, Takuma, 33  
Trnecka, Martin, 18, 24
- Uhlmann, Markus, 14
- Valverde-Albacete, Francisco Jose, 30, 42  
Vargas-Garc a, Edith, 4  
Viaud, Jean-Francois, 25  
Victor, Sandra, 22  
Vincent, Cecile, 6  
Vyjidacek, Roman, 18
- Wachtel, Andreas, 4  
Wannous, Rouaa, 6